

PDS

PRODUCT DATA SHEET





ELG0100 MEC-FLEX UTILITY HIGH VISIBILITY MECHANICS SAFETY GLOVES Mec-Flex Series Glove

PRODUCT CODE	SIZE	
ELG0100M	MEG	
ELG0100L	LRG	
ELG0100XL	XLG	
ELG0100XXL	2XL	

MEC-FLEX UTILITY HIGH VISIBILITY MECHANICS SAFETY GLOVES

Mec-Flex[®] Utility High Vis is a comfortable form fitting glove designed for general day-to-day handling tasks where you need to be seen. The single layer Hyde-Tex 85 palm has silicon fingertips to provide addition grip. The elastic cuff and Hook and Loop TRP closure tab provides a secure fit.

- Two-way form fitting stretch spandex on the back of the hand increasing ventilation, fit and comfort.
- High visibility silver reflective knuckle bar.
- Ventilated finger walls for increased comfort.
- Reinforced synthetic leather thumb, index, middle and ring fingertips.
- Heavy duty elastic cuff with TPR Pull Tab with Hook and Loop closure for secured fit and pulse protection.
- Silicon finger tips for added grip.
- Perforated fourchettes (finger walls).
- Machine washable.

CERTIFICATIONS & STANDARDS

These Gloves are certified by SAI Global to AS/NZS 2161.3:2020 and EN388





General Requirements Risk Category Sizing Marking/labelling etc

E 1912 SZWSY

Mechanical Hazards - Performance Levels						
Test	Level 1	Level 2	Level 3	Level 4	Level 5	
A: Abrasion resistance	100	500	2000	8000	-	
B: Blade cut resistance	1,2	2,5	5,0	10,0	20,0	
C: Tear resistance	10	25	50	75	-	
D: Pucture resistance	20	60	100	150	-	

Information regarding protection refers to the working surface, i.e the palm of the glove which has been submitted for testing. The overall classification for gloves with two or more non-interconnected layers does not necessarily reflect the performance of the outermost layer. The protection levels indicated are only valid for new gloves.



www.elliotts.net



Abrasion resistance Blade cut resistance Tear resistance Pucture resistance

