

Lightweight, frameless protection, ideal for all-day wear



The Pyramex Itek range offers frameless protection, ideal for all-day wear.

- Newly designed ventilated nosepiece allows heat to dissipate from nose bridge to reduce fogging.
- Soft dual injected rubber temple tips and flexible nosepiece provide non-slip comfort.
- Lightweight, frameless protection is ideal for all-day wear.
- Lenses provide 100% protection against UV rays.



ELLIOTTS E QUALITY SAFETY GEAR


PDS













Injected rubber temple tips

ITEK

- Newly designed ventilated nosepiece allows heat to dissipate from nose bridge to reduce fogging.
- Soft dual injected rubber temple tips and flexible nosepiece provide non-slip comfort
- 9.75 base curve lens provides excellent side protection against dust and airbourne particles.
- Lightweight, frameless protection is ideal for all-day wear.
- UV400 lenses provide 100% protection against harmful UV rays.

TECHNICAL SPECIFICATIONS

PRODUCT CODE	PRODUCT DESCRIPTION
AS5810S	CLEAR LENS WITH CLEAR TEMPLES
AS5820S	GREY LENS WITH GREY TEMPLES
AS5830S	AMBER LENS WITH AMBER TEMPLES
MATERIALS	

Lens Polycarbonate - 9.75 base curve

Side Shields Polycarbonate

Nose piece PVC, Pillow softness

Temple Tips Polycarbonate + TPE - Spatula with soft end tip

Hinge Polycarbonate - 3 barrel type

Screw Stainless Steel - Standard hinge screw

PRODUCT SPECIFICATIONS

Lens thickness: 2.3mm PD: 68mm
Lens Base: 9.75 curve Weight: 22gm

Lens size vertical: 43.3mm

Bridge: 12.5mm

Closest point between lens: 16.3mm


Lens size diagonal: 78mm

Temple length (lens-tip): 156mm

Closest point between lens: 16.3mm

CERTIFICATIONS & STANDARDS







ANSI Z87.1-2003 High Impact



SEI Cert. Mod CAN/CSA Z94.3-07



