



PRODUCT DATA SHEET





ELG3310 G-FLEX AIRTOUCH GP G-Flex Series Glove



QUALITY

SAFET GEAR

G-FLEX AIRTOUCH GP

- Lightweight AirTouch Micro-Foam coating provides a comfortable fitting glove.
- Very comfortable with excellent dexterity, sensitivity and tactility.
- Durable nylon 18 gauge seamless liner.
- "Finger Dip" technology gives total ventilation to back of hand.
- Provides highest levels of abrasion-resistance.
- Very comfortable with excellent dexterity, sensitivity and tactility.
- Excellent grip on most surfaces.
- Five sizes with colour coding identification on the cuff of each glove.

PRODUCT CODE	CUFF COLOUR	SIZE
ELG331007	Blue	7
ELG331008	Orange	8
ELG331009	White	9
ELG331010	Yellow	10
ELG331011	Brown	11

CERTIFICATIONS & STANDARDS

These Gloves are certi ied by SAI Global to AS/NZS 2161.3:2005 and EN388





General Requirements Risk Category Sizing Marking/labelling etc



TAKE

Mechanical Hazards - Performance Levels						
Test	Level 1	Level 2	Level 3	Level 4	Level 5	
A: Abrasion resistance	100	500	2000	8000	-	
B: Blade cut resistance	1,2	2,5	5,0	10,0	20,0	
C: Tear resistance	10	25	50	75	-	
D: Pucture resistance	20	60	100	150	-	

Information regarding protection refers to the working surface, i.e the palm of the glove which has been submitted for testing. The overall classification for gloves with two or more non-interconnected layers does not necessarily reflect the performance of the outermost layer. The protection levels indicated are only valid for new gloves.



G-Flex Nitrile