

PRODUCT DATA SHEET



ELG3420

G-FLEX DYNAMAX C5 AIRTOUCH BLUE

G-Flex Dynamax Series Glove

G-FLEX DYNAMAX C5 AIRTOUCH


Lightweight AIRTouch coating to give you the most comfortable fitting glove.

- Dynamax C5 15 Gauge Seamless blue liner.
- Highest Cut level 5 protection.
- "Finger Dip" technology providing ventilation to back of hand.
- Provides highest levels of cut resistance, abrasion and tear resistance. Performance Results 4543
- Extremely comfortable, with excellent dexterity, sensitivity and tactility.
- Excellent surface grip including those with light oil.
- Five sizes with colour coding identification on the cuff of each glove.

MATERIALS

- Dynamax C5 15 gauge liner
- Elasticated Cuff
- AIRTouch Micro Foam Coating

PRODUCT CODE	CUFF COLOUR	SIZE
ELG342007	Blue	7
ELG342008	Orange	8
ELG342009	White	9
ELG342010	Yellow	10
ELG342011	Brown	11



CERTIFICATIONS & STANDARDS

These Gloves are certified by SAI Global to AS/NZS 2161.3:2005 and EN388



AS/NZS 2161.2
EN420



General Requirements
Risk Category
Sizing
Marking/labelling etc

AS/NZS 2161.3
EN388



Mechanical Hazards - Performance Levels

Test	Level 1	Level 2	Level 3	Level 4	Level 5
A: Abrasion resistance	100	500	2000	8000	-
B: Blade cut resistance	1,2	2,5	5,0	10,0	20,0
C: Tear resistance	10	25	50	75	-
D: Puncture resistance	20	60	100	150	-

Information regarding protection refers to the working surface, i.e the palm of the glove which has been submitted for testing. The overall classification for gloves with two or more non-interconnected layers does not necessarily reflect the performance of the outermost layer. The protection levels indicated are only valid for new gloves.

Abrasion resistance
Blade cut resistance
Tear resistance
Puncture resistance

OTHER DYNAMAX CUT RESISTANT GLOVES

			
G-Flex Dynamax C5 AirTouch Fingerless	G-Flex Dynamax Roustabout IMPACT	G-Flex Dynamax Roustabout	G-Flex Dynamax C3 T-Touch Lite