

PRODUCT DATA SHEET



ELG3100  
G-FLEX LITE  
G-Flex Series Glove

G-FLEX LITE

- Extremely comfortable with excellent dexterity, sensitivity and tactility.
- Durable Nylon 18 gauge seamless liner.
- "Finger Dip" technology gives total ventilation to the back of the hand.
- Ultra-lightweight polyurethane coating.
- Good levels of abrasion resistance.
- Provides cut, tear and puncture resistance.

PRODUCT CODE	CUFF COLOUR	SIZE
ELG310007	Blue	7
ELG310008	Orange	8
ELG310009	White	9
ELG310010	Yellow	10
ELG310011	Brown	11


CERTIFICATIONS & STANDARDS


These Gloves are certified by SAI Global to AS/NZS 2161.3:2005 and EN388



OTHER G-FLEX GLOVES



AS/NZS 2161.2 EN420  **General Requirements**  
Risk Category  
Sizing  
Marking/labelling etc

AS/NZS 2161.3 EN388  **Mechanical Hazards - Performance Levels**

Test	Level 1	Level 2	Level 3	Level 4	Level 5
A: Abrasion resistance	100	500	2000	8000	-
B: Blade cut resistance	1,2	2,5	5,0	10,0	20,0
C: Tear resistance	10	25	50	75	-
D: Puncture resistance	20	60	100	150	-

Information regarding protection refers to the working surface, i.e the palm of the glove which has been submitted for testing. The overall classification for gloves with two or more non-interconnected layers does not necessarily reflect the performance of the outermost layer. The protection levels indicated are only valid for new gloves.