

**RAZOR MULTI 250** 





#### **HD Backlit Interface**

Experience a new level of convenience with our next-generation interface panel. With its vibrant and easy-to-read display, you'll be able to effortlessly navigate and customise your welding settings in any lighting condition.

#### **Synergic MIG Control**

Say goodbye to complicated and time-consuming setup with our innovative Synergic MIG control. This cutting-edge technology automatically adjusts your welding settings based on your wire type, gas, wire size, and material thickness, ensuring precise and efficient results every time.

#### **Digital Control MIG Torch**

The ultimate solution for welders seeking unprecedented control and precision in their work. No more hassle of constantly adjusting your settings on a separate control panel. With our leading technology, you can easily fine-tune your amps, wire speed, and voltage right on the MIG torch itself.

#### **Spool Gun Ready**

Attach a Spool Gun to run softer core wires such as aluminium MIG wire. You don't even need to change the setup of your existing torch or drive rollers.

#### **Gas & Gasless MIG**

Our welding machine supports both gas-shielded and gasless MIG wire, allowing you to tackle a wide variety of welding projects with ease. Whether you're working with mild steel, stainless steel, aluminium, or flux-cored wire, our machine has got you covered.

#### **4 Geared Wire Drive**

Experience smooth and consistent wire feeding with our advanced 4 geared roller drive unit. This feature ensures that your wire is fed consistently and accurately, even when using longer MIG torches.

#### **Multi-Process Welding**

Get the job done quickly and efficiently with our versatile threein-one welding machine. With the ability to perform MIG, TIG, and STICK welding all in one unit, you can save valuable time and effort without sacrificing quality.

#### **Foot Control Ready**

Enjoy greater control and precision with our optional foot control accessory. This handy feature allows you to easily adjust your TIG amperage on the fly, without interrupting your torch movement.

#### **Trigger Controlled DC Lift Arc TIG**

With Trigger Controlled DC Lift Arc ignition, starting your welding projects has never been easier. Our Lift Arc TIG technology ensures that your tungsten tip won't stick to the workpiece, preventing costly tip breakages.

#### **Smart Fan**

Our advanced Smart Fan technology reduces noise, saves power, and minimises contaminants, making it the perfect choice for any welding environment.

#### **Advanced MMA Features**

The RAZOR MULTI 250 features adjustable Arc Force and Hot Start functionality. These features are designed for improving weld quality and ease of use.

#### **Optional Remote Control**

Upgrade your machine with a handy remote control. Both a wired and wireless controller are available.



# **RAZOR MULTI 250**

### **SPECIFICATIONS**

### **Technical Data**

| Parameter               | Values                 |
|-------------------------|------------------------|
| SKU                     | U11009K                |
| Primary Input Voltage   | 240V Single Phase      |
| Supply Plug             | 15 AMP                 |
| leff (A)                | 15                     |
| Rated Output            | 30A/15.5V - 250A/26.5V |
| No Load Voltage (V)     | 65                     |
| Protection Class        | IP23S                  |
| Insulation Class        | Н                      |
| Minimum Generator (kVA) | 11.0                   |
| Dinse Connector         | 35/50                  |
| Standard                | AS/NZ60974-1           |
| Warranty (Years)        | 5                      |

### **MIG Specifications**

| MIG Welding Current Range   | 30-250A                                 |
|-----------------------------|---|
| MIG Duty Cycle @ 40°C       | 20% @ 250A<br>60% @ 144A<br>100% @ 112A |
| MIG Welding Thickness Range | 1-12mm                                  |

## **TIG Specifications**

| TIG Function Type           | DC Lift Arc                             |
|-----------------------------|---|
| TIG Welding Current Range   | 5-250A                                  |
| TIG Duty Cycle @ 40°C       | 20% @ 250A<br>60% @ 144A<br>100% @ 112A |
| TIG Welding Thickness Range | 1-10mm                                  |

## **STICK Specifications**

| STICK Welding Current Range   | 20-220A                                |
|-------------------------------|--|
| STICK Duty Cycle @ 40°C       | 20% @ 220A<br>60% @ 127A<br>100% @ 98A |
| STICK Welding Thickness Range | 2-12mm                                 |

## Size & Weight

| Dimensions (mm) | 700x280x511 |
|-----------------|-------------|
| Weight (kg)     | 25.5        |

### **Capable Welding Material Types By Welding Process**